

DA 2668

Extractor unit

with energy-efficient LED lighting and light-touch switches for easy use.



- Customised kitchen design - fully integrated in 580mm width
- Unique user convenience – Con@ctivity
- Powerful - 585m<sup>3</sup>/h on the booster setting
- Energy-efficient and quiet - powerful ECO motor
- Efficient filtration- 10-ply stainless-steel grease filter

EAN: 4002516001522 / article number: 28266855GB / material number: 10851380

|   |                 |
|---|-----------------|
| <b>Construction type</b>  |                 |
| Integrated extractor  | •               |
| <b>Design</b>   |                 |
| Colour  | Stainless steel |
| Edge extraction   | •               |
| <b>Operating modes</b>  |                 |
| Type of air guide   | Convertible     |
| Active charcoal filter (order separately)   | DKF19-1         |
| <b>User convenience</b>   |                 |
| Electronic controls   | •               |
| Light-touch controls  | •               |
| Miele@mobile app  | •               |
| Power levels (number without Booster level)   | 3               |
| Booster level   | •               |
| Programmable Booster level switch-off   | •               |
| Run-on time 5 / 15 min.   | •               |
| Grease filter saturation indicator programmable   | •               |
| Active charcoal filter saturation indicator programmable                                    | •               |
| <b>Cleaning convenience</b>   |                 |
| Easy-to-clean canopy interior – CleanCover  | •               |
| <b>Efficiency and sustainability</b>  |                 |
| Annual energy consumption in kWh/year   | 28,4            |
| ECO package   | •               |
| <b>Filter system</b>  |                 |
| Number of dishwasher safe stainless steel grease filters                                    | 2               |
| <b>Lighting</b>   |                 |
| LED   | •               |
| Number x W  | 2 x 4,5 W       |
| Light intensity in lx   | 700             |
| Colour temperature in K   | 3.500           |
| Dimmer function   | •               |
| <b>Fan</b>  |                 |
| Dual-action fan   | •               |
| ECO motor (DC motor)  | •               |
| <b>Air throughput with max. duct diameter in extraction mode (not for external version)</b> |                 |
| Air throughput in Level 1 (m <sup>3</sup> /h)   | 175             |
| Air throughput in Level 2 (m <sup>3</sup> /h)   | 265             |
| Air throughput in Level 3 (m <sup>3</sup> /h)   | 365             |
| Air throughput in Booster level (m <sup>3</sup> /h)   | 585             |
| Sound power in Level 1 (dB(A) re 1 pW)  | 35              |
| Sound power in Level 2 (dB(A) re 1 pW)  | 44              |
| Sound power in Level 3 (dB(A) re 1 pW)  | 51              |
| Sound power in Booster level (dB(A) re 1 pW)  | 64              |
| Sound pressure in Level 1 (dB(A) re 20 µPa)   | 21              |
| Sound pressure in Level 2 (dB(A) re 20 µPa)   | 29              |
| Sound pressure in Level 3 (dB(A) re 20 µPa)   | 37              |
| Sound pressure in Booster level (dB(A) re 20 µPa)   | 50              |

DA 2668

Extractor unit

with energy-efficient LED lighting and light-touch switches for easy use.



|   |             |
|---|-------------|
| <b>Air throughput in recirculation mode</b>                                     |             |
| Air throughput in Level 1 (m <sup>3</sup> /h)                                   | 115         |
| Air throughput in Level 2 (m <sup>3</sup> /h)                                   | 200         |
| Air throughput in Level 3 (m <sup>3</sup> /h)                                   | 330         |
| Air throughput in Booster level (m <sup>3</sup> /h)                             | 490         |
| Sound power in Level 1 (dB(A) re 1 pW)  | 46          |
| Sound power in Level 2 (dB(A) re 1 pW)  | 56          |
| Sound power in Level 3 (dB(A) re 1 pW)  | 64          |
| Sound power in Booster level (dB(A) re 1 pW)                                    | 74          |
| Sound pressure in Level 1 (dB(A) re 20 µPa)                                     | 32          |
| Sound pressure in Level 2 (dB(A) re 20 µPa)                                     | 42          |
| Sound pressure in Level 3 (dB(A) re 20 µPa)                                     | 49          |
| Sound power in Booster level (dB(A) re 1 pW)                                    | 60          |
| <b>Safety</b>   |             |
| Safety switch-off   | •           |
| <b>Technical data</b>   |             |
| Canopy width in mm  | 580         |
| Canopy height in mm   | 64          |
| Canopy depth in mm  | 293         |
| Minimum height above electric hobs in mm  | 450         |
| Minimum height above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm | 650         |
| Net weight in kg  | 12,0        |
| Length of supply lead in m  | 1,5         |
| Standard plug fitted  | •           |
| Total rated load in kW  | 0,09        |
| Voltage in V  | 230         |
| Fuse rating in A  | 10          |
| Frequency in Hz   | 50          |
| Number of phases  | 1           |
| <b>Installation notes</b>   |             |
| Extraction ducting connection at top  | •           |
| Extraction connection at top and rear   | •           |
| Diameter of extraction ducting connection in mm                                 | 150         |
| Combination with WiFi-enabled Miele hob   | recommended |
| <b>Standard accessories</b>   |             |
| Non-return flap   | •           |