

PUR 98 W

Wall mounted cooker hood

with energy-efficient LED lighting and light-touch switches for easy use.



- Timeless design - 898mm wide stainless steel cooker hood
- Powerful - 650m³/h on the booster setting
- Efficient filtration- 10-ply stainless-steel grease filter
- Safe and easy to clean - Miele CleanCover
- Suitable for every home - for extraction or recirculation

EAN: 4002515752791 / article number: 28419854GB / material number: 10434520

Construction type	
Wall mounted cooker hood	•
Design	
Colour	Stainless steel
RAL colours available as customisation on request	•
Customisation possible on request	•
Operating modes	
Type of air guide	Convertible
Active charcoal filter (order separately)	DKF12-1
User convenience	
Electronic controls	•
Light-touch controls	•
Power levels (number without Booster level)	3
Booster level	•
Programmable Booster level switch-off	•
Cleaning convenience	
Easy-to-clean canopy interior – CleanCover	•
Efficiency and sustainability	
Annual energy consumption in kWh/year	49,7
Filter system	
Number of dishwasher safe stainless steel grease filters	3
Lighting	
LED	•
Number x W	3 x 3 W
Light intensity in Lx	450
Colour temperature in K	3.000
Fan	
Dual-action fan	•
AC motor	•
Air throughput with max. duct diameter in extraction mode (not for external version)	
Air throughput in Level 1 (m ³ /h)	265
Air throughput in Level 2 (m ³ /h)	320
Air throughput in Level 3 (m ³ /h)	395
Air throughput in Booster level (m ³ /h)	650
Sound power in Level 1 (dB(A) re 1 pW)	47
Sound power in Level 2 (dB(A) re 1 pW)	52
Sound power in Level 3 (dB(A) re 1 pW)	56
Sound power in Booster level (dB(A) re 1 pW)	67
Sound pressure in Level 1 (dB(A) re 20 µPa)	32
Sound pressure in Level 2 (dB(A) re 20 µPa)	37
Sound pressure in Level 3 (dB(A) re 20 µPa)	41
Sound pressure in Booster level (dB(A) re 20 µPa)	52

PUR 98 W

Wall mounted cooker hood
with energy-efficient LED lighting and light-touch switches for easy use.




Air throughput in recirculation mode	
Air throughput in Level 1 (m³/h)	190
Air throughput in Level 2 (m³/h)	270
Air throughput in Level 3 (m³/h)	330
Air throughput in Booster level (m³/h)	460
Sound power in Level 1 (dB(A) re 1 pW)	54
Sound power in Level 2 (dB(A) re 1 pW)	60
Sound power in Level 3 (dB(A) re 1 pW)	64
Sound power in Booster level (dB(A) re 1 pW)	71
Sound pressure in Level 1 (dB(A) re 20 µPa)	39
Sound pressure in Level 2 (dB(A) re 20 µPa)	45
Sound pressure in Level 3 (dB(A) re 20 µPa)	48
Sound power in Booster level (dB(A) re 1 pW)	56
Safety	
Safety switch-off	•
Technical data	
Overall height for extraction mode and external mode cooker hoods in mm	685
Overall height for recirculation mode cooker hoods in mm	815
Canopy width in mm	898
Canopy height in mm	62
Canopy depth in mm	500
Minimum height above electric hobs in mm	450
Minimum height above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm	650
Net weight in kg	25,0
Length of supply lead in m	1,5
Standard plug fitted	•
Total rated load in kW	0,23
Voltage in V	230
Fuse rating in A	10
Frequency in Hz	50
Number of phases	1
Installation notes	
Extraction ducting connection at top	•
Extraction connection at top and rear	•
Diameter of extraction ducting connection in mm	150
Telescopic chimney	•
Standard accessories	
Non-return flap	•
Adapter to reduce ducting diameter from 150 mm to 125 mm Ø	•

PUR 98 W

Wall mounted cooker hood

with energy-efficient LED lighting and light-touch switches for easy use.



DA 419-6, DA 419-7 (Installation drawing)

- 1) Extraction
- 2) Recirculation
- 3) Ventilation grille at top for recirculation
- 4+5) Installation cut-out (5 not required for recirculation)